



## Price list

Effective 01.DEC.2020

### Monoblock Amplifiers

Analog Domain monoblock amplifiers are among the most advanced audio amplifiers today. They offer extreme power output while preserving the character of the performance at any output level. The proprietary DX9 bias control method ensures a stable operating point for the power stages, regardless of load, temperature or voltage variations. Proprietary supply management ensures optimal performance, enabling the amplifiers to deliver considerably higher, distortion-free power output than similar sized units while keeping heat output to a minimum and thus maximizing the life of components. Analog Domain DX9 amplifiers are built to the highest standards and come with a 10-year manufacturer's warranty covering any defects in materials or workmanship.



### Calysto and Artemis, M2R4 Chassis

**1 CALYSTO single-channel audio amplifier**

550W/8 ohm, 1000W/4ohm, M2R4 chassis, 1x RCA input, 1x XLR-F input, 1x XLR-M pass thru, 3.5mm jacks for remote trigger In/Out 12V, gain selector Full/26dB, IEC C14 Power inlet w/line filter. Thermal circuit breaker. 230V/115V factory preset. Standard finish: mirror chrome  
 Warranty: 10 years parts & labor. Dimensions: 440(w) x 600(d) x 250(h), mm. Net weight ca. 58kg  
 Packaging: flight case. Power cord not included!

		<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
1.1	Black:	CA-R2BK	57'067	68'480
1.2	Chrome:	CA-R2CR	58'317	69'980
<i>Price is for one unit!</i>				

**2 ARTEMIS single-channel audio amplifier**

1000W/8 ohm, 2000W/4ohm, M2R4 chassis, 1x RCA input, 1x XLR-F input, 1x XLR-M pass thru, 3.5mm jacks for remote trigger In/Out 12V, gain selector Full/26dB, IEC C14 Power inlet w/line filter. Thermal circuit breaker. 230V/115V factory preset. Standard finish: mirror chrome  
 Warranty: 10 years parts & labor. Dimensions: 440(w) x 600(d) x 250(h), mm. Net weight ca. 60kg.  
 Packaging: flight case. Power cord not included!

		<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
2.1	Black:	AR-R2BK	69'575	83'490
2.2	Chrome:	AR-R2CR	70'825	84'990
<i>Price is for one unit!</i>				



## Extreme power output monoblock amplifiers

The Athene and Apollo are our statement monoblock amplifiers. They are among the most powerful amplifiers ever built for high end audio, offering extreme power while delivering music with perfect control and finesse at any output level. Proprietary voltage management technology keeps heat output at a minimum while providing ultimate performance.



Athene and Apollo, M4R4 Chassis

### 3 ATHENE single-channel audio amplifier

2000W/8 ohm, 4000W/4ohm, M4R4 chassis, 1x RCA input, 1x XLR-F input, 1x XLR-M pass thru, 3.5mm jacks for remote trigger In/Out 12V, gain selector Full/26dB, IEC C14 Power inlet w/line filter. Thermal circuit breaker. 230V/115V factory preset. Standard finish: mirror chrome.

Warranty: 10 years parts & labor. Dimensions: 440(w) x 600(d) x 295(h), mm. Net weight ca. 70kg.

Packaging: flight case. Power cord not included!

3.1

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
Black:	AT-R2BK	81'242	97'490

3.2

Chrome:	AT-R2CR	82'492	98'990
---------	---------	--------	--------

*Price is for one unit!*

### 4 APOLLO single-channel audio amplifier

4000W/8 ohm, 8000W/4ohm, M4R4 chassis, 1x RCA input, 1x XLR-F input, 1x XLR-M pass thru, 3.5mm jacks for remote trigger In/Out 12V, gain selector Full/26dB, IEC C14 Power inlet w/line filter. Thermal circuit breaker. 230V/115V factory preset. Standard finish: mirror chrome.

Warranty: 10 years parts & labor. Dimensions: 440(w) x 600(d) x 295(h), mm. Net weight ca. 85kg.

Packaging: flight case. Power cord not included!

4.1

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
Black:	AP-R2BK	102'908	123'490

4.2

Chrome:	AP-R2CR	104'158	124'990
---------	---------	---------	---------

*Price is for one unit!*



## Dual channel integrated amplifiers

The Isis M75 range of amplifiers are state of the art audio amplifiers feature our proprietary Excalibur output circuit, which couples extreme output capability with perfect control. The DX9 bias control method and managed power supply ensure outstanding performance with greatly improved thermal efficiency, thus maximizing component life.

The M75 range includes the M75D integrated amplifier and M75P power amplifier. Both models can be configured as stereo or as single channel amplifiers in bridged mode when higher power output is required. Stable into 2 ohms in stereo mode. Analog Domain M75 amplifiers are built to the highest standards and are backed by a 5-year manufacturer's warranty.



Isis M75DW (Silver)



Isis M75DK (Black)

### 5 ISIS dual-channel integrated audio amplifier model M75D

2x 250W/8 ohm, 2x 400W/4ohm, 1x500W/8ohm, 1x800W/4ohm in bridged mode  
 M7 chassis, 2x RCA inputs with individual gain selection, 2x XLR-F inputs, 2x XLR-5 in/out, 3.5mm jacks  
 trigger In/Out 12V, IEC C14 Power inlet. 230V/115V selectable. IR remote control.  
 Warranty: 5 years parts & labor. Dimensions: 440(w) x 450 (d) x 125 (h). NW 21kg. GW 30kg.  
 Packaging: Flight case. Power cord not included!

		<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
5.1	Silver:	M75DW	17'492	20'990
5.2	Satin Black:	M75DK	17'492	20'990



## Dual channel power amplifiers

The Isis M75P power amplifiers feature the same technology as in the M75D range, yet they offer a pure signal path from the inputs to the power stages for unaltered delivery of audio signals. They are the ideal choice for driving multi-way active speaker systems or multi-channel home cinema setups. When configured as a single channel mono amplifier, the Isis M75P will deliver up to 800W into a 4 ohm load. Stable into 2 ohms in stereo mode.



Isis M75PW (Silver)



Isis M75PK (Black)

### 6 ISIS dual-channel audio power amplifier model M75P

2x 250W/8 ohm, 2x 400W/4ohm, 1x500W/8, 1x800W/4 in bridged mode  
 M7 chassis, 1x RCA input +1x RCA pass thru, 1x XLR-F input + 1x XLR-M pass thru, 2x XLR-5 in/out, 3.5mm jacks for remote trigger In/Out 12V, gain selector on RCA inputs, IEC C14 Power inlet. 230V/115V user selectable. Warranty: 5 years parts & labor. Dimensions: 440(w) x 440 (d) x 125 (h). NW 20kg. GW 29kg. Packaging: Flight case. Power cord not included!

		<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
6.1	Silver	M75PW	15'825	18'990
6.2	Satin Black:	M75PK	15'825	18'990



## Digital front end

The Analog Domain DAC1 is a high performance asynchronous mode digital to analog converter, designed for faithful reproduction of digitized music. It will accept all current and future digital formats up to 192kHz/24bits over S/PDIF and AES/EBU, DXD (384kHz/32bits) and DSD256 (4x) over USB. The USB port is supported in the kernel with IOS- and Linux-based systems.



DAC1V - with analog volume control



DAC1 - no volume control

### 7 DAC1V digital to analog converter with volume control

1xUSB, 1xTOSLINK S/PDIF, 2xRCA S/PDIF, 1xAES/EBU inputs. 2xRCA, 2xXLR analog outputs.  
 MD7 chassis, 127 step analog volume control, 3.5mm sockets for trigger In/Out 12V, IEC C14 Power inlet.  
 230V/115V user selectable. IR remote control. Warranty: 5 years parts & labor. NW 10kg, Flight case,  
 GW19kg. Dimensions: 440(w) x 450 (d) x 85 (h), mm. Power cord not included!

		P/N	EXW Base	MSRP
7.1	Silver	DAC1VW	17'075	20'490
7.2	Satin Black:	DAC1VK	17'075	20'490
<b>8 DAC1 digital to analog converter, no volume control</b>				
8.1	Silver	DAC1NVW	15'417	18'500
8.2	Satin Black:	DAC1NVK	15'417	18'500
9	Volume control upgrade of DAC1 to DAC1V (factory install only)	DACVOL	1'658	1'990



## Loudspeakers

### Argus

Reference 3-way high output loudspeaker system, designed for realistic playback up to live sound levels.

2x 12" woofers, 6.5" midrange, AMT tweeter, adjustable frequency response. Bi-amp / bi-wire ready.

Rated impedance: 4 ohm. Nominal efficiency: 99dB/2.83V @ 1m. Warranty 10 years parts & labor.

Available in Brushed Black, Brushed Titanium or custom finish. *\*Some feature colours may vary from illustration*

Shown without deco grilles (included). NW: 65kg, each. Dimensions: 440w x 440d x 1200h, mm



10.1  
10.2  
10.3

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
Argus pair, brushed black:	AG-BK	39'958	47'950
Argus pair, brushed titanium:	AG-TN	39'958	47'950
Argus pair, black crystal:	AG-XS	49'958	59'950



## Aura

Reference 2-way loudspeaker system, offering realistic reproduction in a compact format.  
8" woofer, 1" tweeter, adjustable frequency response. Bi-amp / bi-wire ready.  
Rated impedance: 8 ohm. Nominal efficiency: 92dB/2.83V @ 1m. Warranty 10 years parts & labor.  
Available in Brushed Black or Brushed Titanium finish. Includes stands.  
NW: 25kg, each incl. stand. Dimensions: 230w x 340d x 1050h, mm. Packaging: carton.



11.1  
11.2  
11.3

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
Aura pair, brushed black:	AU-BK	12'458	14'950
Aura pair, brushed titanium:	AU-TN	12'458	14'950
Custom finishing (piano finish):	AU-CX	16'625	19'950



## Cables and accessories



**Interlink X5-S, XLR-5M to XLR-5F audio signal cable**  
provides a direct connection between Isis amplifiers via a single cable connection.

12.1  
12.2  
12.3

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
Length 0.7m:	X5-M	458	549
Length 1.5m:	X5-L	541	649
Length 3m:	X5-XL	583	699



**13 X5-OUT, XLR-5F to 2x XLR-3M audio signal cable, Length 0.3m**  
provides an output from the preamplifier of the Isis on two standard 3-pin XLR male connectors

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
	X5-OUT	416	499



**14 X5-IN, XLR-5M to 2x XLR-3F audio signal cable, Length 0.3m**  
provides an input to the power stages of the Isis on two standard 3-pin XLR female connectors

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
	X5-IN	416	499

**15 Remote link, 3.5mm to 3.5mm plugs**  
enables remote power on/off of connected devices via trigger voltage

15.1  
15.2  
15.3

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
Length 0.7m:	RL-M	24	29
Length 3m:	RL-L	33	39
Length 6m:	RL-XL	41	49

**Accessory and cable prices assume shipping with main order. Single orders may be subject to shipping charges.**

*MSRP: suggested retail prices in EUR incl. VAT. EXW Base: the basis for calculating the net price excl VAT.*