

Price list 2026

EXW prices in EURO, ex VAT. MSRP for reference only



Ultimate performance power amplifiers

Analog Domain amplifiers are among the most advanced audio amplifiers today. They rendering music with ultimate fidelity at any output level. The proprietary DX-Drive™ bias control method ensures a stable operating point for the power stages, regardless of load, temperature or voltage variations. Proprietary supply management enables the amplifiers to deliver very high power, while keeping heat output to a minimum, thus maximizing the life of components. Recent breakthroughs in circuit technology has brought distortion to barely measurable levels in single-ended mode, therefore we've added this option.

Ultimate performance is achieved in bridged mono mode.

Analog Domain DX9 amplifiers are built to the highest standards and are covered by a 10-year manufacturer's warranty for any defects in materials or workmanship.



ATHENE Dual mode power amplifier

Power output in mono mode: 1x 2000W/8ohm, 1x 4000W/4ohm

Power output in stereo mode: 2x 500W/8ohm, 2x 1000W/4ohm

Gain: +34dB in stereo mode; +40dB in mono mode

Inputs: 2x RCA inputs, 2x XLR inputs, 2x 3.5mm jacks for remote trigger In/Out 12V,

IEC C14 Power inlet. 230V/115V, factory preset. Finishing options: Chrome, Black

Warranty: 10 years parts & labor. Power cord not included.

M4R5 chassis: 440(w) x 600(d) x 295(h), mm. Net weight ca. 70kg. Packaging: flight case.

EXW Base

145'000

MSRP

174'000

APOLLO Dual mode power amplifier

Power output in monoblock mode: 1x 4000W/8ohm, 1x 8000W/4ohm

Power output in stereo mode: 2x 1000W/8ohm, 2x 2000W/4ohm

Gain: selectable +34dB in stereo mode; +40dBdB in mono mode

Inputs: 2x RCA inputs, 2x XLR inputs, 2x 3.5mm jacks for remote trigger In/Out 12V,

IEC C14 Power inlet. 230V/115V, factory preset. Finishing options: Chrome, Black

Warranty: 10 years parts & labor. Power cord not included.

M4R5 chassis: 440(w) x 600(d) x 295(h), mm. Net weight ca. 84kg. Packaging: flight case.

EXW Base

180'000

MSRP

216'000



P1 Reference preamplifier

The **P1 Reference** is the ultimate driving source for power amplifiers. It has been designed for exceptional performance and longevity. Inputs feature individual gain control for matching the output levels of connected sources and maximum dynamic range. The P1 has connections for two independent recording devices or external processors. A dedicated AUX input with switchable volume bypass allows integration with an AV system.

The **P1 Reference** will support a total of nine sources, featuring RCA and XLR connections. The signal path is all-analog, built with premium components. There are no capacitors or mechanical switches in the signal path. Volume control is via a logarithmic stepped resistor matrix using solid state relays for distortion- and noise-free performance.



P1 Specifications overview

- 3x RCA line inputs, 3x XLR line inputs, 1x XLR, 1x RCA Tape In/Out, all with gain control;
- 1x AUX RCA input w Volume bypass for AV processor connection;
- 1x XLR Mix out for subwoofer connection;
- 2 x 3.5mm Trigger Out sockets;
- RCA and XLR Outputs.
- IEC C14 Power inlet. 230V/115V user-selectable
- Finishing: black. Optional: chrome.
- Warranty: 10 years parts & labor. Dimensions: 440(w) x 440(d) x 135(h), mm.
- Net weight ca. 25kg. Packaging: flight case. Power cord not included.

EXW Base
82'000

MSRP
98'400



P1 Rear view



M75 integrated amplifiers

The Isis M75 range of amplifiers are state of the art audio amplifiers feature our proprietary Excalibur output circuit, which couples extreme output capability with perfect control. The DX bias control method and managed power supply ensure outstanding performance with greatly improved thermal efficiency, thus maximizing component life. The M75 range includes the M75D integrated amplifier and M75P power amplifier. Both models can be configured as single channel amplifiers in bridged mode when higher power output is required.

Stable into 2 ohms in stereo mode.

Analog Domain M75 amplifiers are built to the highest standards and carry a 5-year manufacturer's warranty.



Isis M75D, Silver



M75D Rear view

ISIS dual-channel integrated audio amplifier model M75D
 2x 250W/8 ohm, 2x 400W/4ohm, 1x 500W/8ohm, 1x 800W/4ohm bridged
 M7 chassis, 2x RCA inputs with individual gain selection, 2x XLR inputs,
 2x XLR-5 Main-in/ Pre-out connectors, 2x 3.5mm jacks trigger In/Out 12V,
 IEC C14 Power inlet. 230V/115V selectable. IR remote control.
 Warranty: 5 years parts & labor. Dimensions: 440(w) x 450 (d) x 125 (h).
 Net weight 21kg. GW 30kg.
 Packaging: Flight case. Power cord not included!

EXW Base
23'500

MSRP
28'200



M75 power amplifiers

The Isis M75P power amplifiers feature the same topology as the M75D. They offer a direct signal path from the inputs to the power stages for unaltered delivery of audio signals. They are the ideal choice for driving multi-way active speaker systems or multi-channel home cinema setups. When configured as a single channel mono amplifier, the Isis M75P will deliver up to 800W into a 4 ohm load. Stable into 2 ohms in stereo mode.



Isis M75P, Silver



Isis M75P Rear view

ISIS dual-channel audio power amplifier model M75P

2x 250W/8 ohm, 2x 400W/4ohm, 1x 500W/8, 1x 800W/4 bridged

M7 chassis, 1x RCA input +1x RCA pass thru, 1x XLR-F input + 1x XLR-M pass thru, 2x XLR-5 in/out, 2x 3.5mm jacks for remote trigger In/Out 12V,

Gain selector on the RCA inputs, IEC C14 Power inlet. 230V/115V user selectable.

Warranty: 5 years parts & labor. Dimensions: 440(w) x 440 (d) x 125 (h).

Net weight 20kg. GW 29kg. Packaging: Flight case.

Power cord not included

EXW Base
21'000

MSRP
25'200



Digital front end

The Analog Domain DAC1 is a high performance asynchronous mode digital to analog converter, designed for faithful reproduction of digitized music. It will accept all current and future digital formats up to 192kHz/24bits over S/PDIF and AES/EBU, DXD (384kHz/32bits) and DSD256 (4x) over USB. The USB port is supported in the kernel with IOS- and Linux-based systems. Windows drivers included.



DAC1V - with analog volume control



DAC1 - Line level output



Rear view

DAC1V digital to analog converter with volume control

1x USB, 1x TOSLINK, 2x RCA S/PDIF, 1x AES/EBU inputs.

RCA and XLR analog outputs.

MD7 chassis, 127 step analog volume control, 2x 3.5mm sockets for trigger In/Out 12V, IEC C14 Power inlet. 230V/115V user selectable. IR remote control.

Dimensions: 440(w) x 450 (d) x 85 (h), mm.

Warranty: 5 years parts & labor. NW 10kg. Power cord not included

EXW Base

24'500

MSRP

29'400.00

DAC1 digital to analog converter, line level output

Specifications as above, no volume control

EXW Base

23'000

MSRP

27'600.00



Loudspeakers

The Argus

Reference 3-way, high output loudspeaker system. Designed for realistic playback up to live sound levels.

2x 12" woofers, 6.5" midrange, AMT tweeter, adjustable frequency response. Bi-amp / bi-wire ready.

Rated impedance: 4 ohm. Nominal efficiency: 99dB/2.83V @ 1m. Warranty 10 years parts & labor.

Available in Brushed Black or Titanium.

Shown without deco grilles (included). NW: 65kg, each. Dimensions: 440w x 440d x 1200h, mm



	<u>EXW Base</u>	<u>MSRP</u>
Pair, brushed black:	75'000	90'000
Pair, brushed titanium:	75'000	90'000



The Aura

The Aura is a reference 2-way loudspeaker system, offering realistic reproduction in a compact format.
8" woofer, 1" tweeter, adjustable frequency response. Bi-amp / bi-wire ready.

Rated impedance: 8 ohm. Nominal efficiency: 92dB/2.83V @ 1m. Warranty 10 years parts & labor.

Available in Brushed Black or Brushed Titanium finish. Includes stands.

NW: 25kg, each incl. stand. Dimensions: 230w x 340d x 1050h, mm. Packaging: carton.



	<u>EXW Base</u>	<u>MSRP</u>
Pair, black:	15'000	18'000
Pair, titanium:	15'000	18'000



Cables and accessories



Interlink X5-S, XLR-5M to XLR-5F audio signal cable
provides a direct connection between Isis amplifiers via a single cable connection.

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
Length 0.7m:	X5-M	450	540
Length 1.5m:	X5-L	550	660
Length 3m:	X5-XL	650	780



X5-OUT, XLR-5F to 2x XLR-3M audio signal cable, Length 0.3m
provides an output from the preamplifier of the Isis on two standard 3-pin XLR male connectors

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
	X5-OUT	450	540



X5-IN, XLR-5M to 2x XLR-3F audio signal cable, Length 0.3m
provides an input to the power stages of the Isis on two standard 3-pin XLR female connectors

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
	X5-IN	450	540

Remote link for trigger connection, 3.5mm to 3.5mm plugs
enables remote power on/off of connected devices via trigger I/O

	<u>P/N</u>	<u>EXW Base</u>	<u>MSRP</u>
Length 0.7m:	RL-M	80	96
Length 3m:	RL-L	100	120
Length 6m:	RL-XL	120	144